



**air turbine spindles®** for



**25,000 – 90,000 rpm – power to 1.60 hp**  
**Constant Governed High Speed and Torque**

*New High Speed Option with Air Turbine Spindles®*

*Ingresso dell'aria laterale o posteriore*



**625(X)HSK**  
0.40 - 0.78 hp



**650(X)HSK**  
0.80 - 1.40 hp



**NEW - 660 Series**  
50,000 rpm  
Power to 1.60 hp  
Quadruple ceramic bearings standard

*With patented governed high speed and torque Air Turbine Spindles®, your Hermle Machine is a high speed machine!*

*No Duty Cycle*

*Call for a Demonstration*

*Fully automated loading:*

1. With our patent pending Toolchanger Mounting Assembly (TMA) or
2. Using coolant channel through center inlet

*Manual Connection also Possible*

**Manual or Automatic Loading to Save Time and Money**



**650HSK**



*Ask about the 602 Series available to 90,000 rpm*




*Dramatically reduce your cycle times, optimize cutting tool performance and life.*

*Keep continuous tool path engagement on your existing CNC at high speed even in angles and hard material. Ideal for micro machining. 25,000 - 90,000 rpm < 1.60 hp (1.19 kW)*

## Accuracy

Most of the problems that occur in micro machining come from a lack of RPM and poor dynamic runout. **Air Turbine Spindles®** use the highest quality runout and balancing systems on the market today. This creates the best dynamic runout accuracy and governed high speed precision.

Runout measured at the nose of spindle. (reference value)



**600 SERIES**

Improved Machining Cycle Times

Better Surface Finish

Longer Tool Life

Automatic Loading

## Super Low Vibration Design

Powerful, totally oil-free low friction motor produces extremely low vibration and heat in continuous 24/7 operation. No thermal expansion, great reliability.



625 - 65,000 rpm

**Ultra Precision ER 8 or ER 11 collets standard.**

## Environmentally Clean

No oil required, and maintenance free.

**Air Pressure:** Dry, Clean Air @ 90 psi (6.2 bar)

**Air Consumption (Working):**

**625(X):** 11 - 30 cfm (5.20 - 14.16 L/s)

**650(X):** 14 - 40 cfm (6.60 - 18.89 L/s)


**660(X):** 14 - 40 cfm (6.60 - 18.89 L/s)

**Low Noise Design:** Under 67 dBA (cutting noise of endmills can be heard).

**Standard Equipment:** 0.3µm High Flow Filter/Extractor

## Automatic Toolchanger

No need for operator downtime. Automatically load **Air Turbine Spindles®** using center airfeed or with our wrap around **Toolchanger Mounting Assembly (TMA)**.



650 - 40,000 rpm

## Superior Technology

- Unique patented direct drive with no vanes, gears or brushes to wear, burn or break.
- Cooled by turbine air for 24/7 operation. No oil or control system required. No Duty Cycle.
- Governor keeps Constant High Speed + Torque on tool path in angles and corners.
- Center Airfeed using coolant channel or Side Airfeed using Automatic Spindle Loading TMA.

## Spindle Selection

√ = Optimum

∞ = Acceptable

! = Dependent upon cutting conditions

x = Not recommended for use

		625(X)	650(X)	660(X)
Drill	Ø 0.1 - 0.3mm	√	√	√
	Ø 0.3 - 0.5mm	√	√	√
	Ø 0.5 - 1.0mm	√	√	√
	Ø 1.0 - 1.5mm	∞	√	√
	Ø 1.5 - 2.0mm	!	√	√
Endmill	Ø 0.1 - 1.0mm	√	√	√
	Ø 1.0 - 2.0mm	√	√	√
	Ø 2.0 - 3.5mm	√	√	√
	Ø 3.5 - 5.0mm	∞	√	√
	Ø 5.0 - 6.0mm	!	∞	∞
Jig Grinding		!	√	√
Specifications	625(X)	650(X)	660(X)	
Speed (rpm)	30,000 40,000 50,000 65,000	25,000 30,000 40,000	50,000	
Power (hp)	0.40 - 0.78	0.80 - 1.40	0.94 - 1.60	
T.I.R. at Nose	Less than 2µm			
Collet Range	0.5mm - 7mm			
Air Pressure	Less than 6.2 Bar (0.62 MPa)			
Air Flow	11 - 40 cfm (5.20 - 18.89 L/s) [ANR]			

