



air turbine spindles[®] for HURCO[®]

25,000 – 90,000 rpm – power to 1.60 hp
Constant Governed High Speed and Torque

Now your Hurco VM/VMX CNC delivers faster production 24/7



625(X)CAT40
0.40 - 0.78 hp



650(X)CAT40
0.80 - 1.40 hp



NEW - 660 Series
50,000 rpm
Power to 1.60 hp
Quadruple ceramic bearings standard

With patented governed high speed and torque Air Turbine Spindles[®], your Hurco VM/VMX Machine is a high speed machine!

No Duty Cycle
Call for a Demonstration


Fully automated loading: With our patent pending Toolchanger Mounting Assembly (TMA)

CAT, BT, DIN, HSK available
Manual Connection also Possible


Manual or Automatic Loading to Save Time and Money



Hurco VM10i



625CAT
50,000 rpm, 0.50 hp



Ask about the 602 Series
available to 90,000 rpm




Dramatically reduce your cycle times, optimize cutting tool performance and life.

Keep continuous tool path engagement on your existing CNC at high speed even in angles and hard material. Ideal for micro machining. 25,000 - 90,000 rpm < 1.60 hp

Accuracy

Most of the problems that occur in micro machining come from a lack of RPM and poor dynamic runout. **Air Turbine Spindles®** use the highest quality runout and balancing systems on the market today. This creates the best dynamic runout accuracy and governed high speed precision.

Runout measured at the nose of spindle. (reference value)



600 SERIES

Improved Machining Cycle Times

Better Surface Finish

Longer Tool Life

Automatic Loading

Super Low Vibration Design

Powerful, totally oil-free low friction motor produces extremely low vibration and heat in continuous 24/7 operation. No thermal expansion, great reliability.



625 - 50,000 rpm

Ultra Precision ER 8 or ER 11 collets standard.

Environmentally Clean

No oil required, and maintenance free.

Air Pressure: Dry, Clean Air @ 90 psi (6.2 bar)

Air Consumption (Working):

625(X): 11 - 30 cfm (5.20 - 14.16 L/s)

650(X): 14 - 40 cfm (6.60 - 18.89 L/s)

660(X): 14 - 40 cfm (6.60 - 18.89 L/s)

Low Noise Design: Under 67 dBA (cutting noise of endmills can be heard).

Standard Equipment: 0.3µm High Flow Filter/Extractor

Automatic Toolchanger

No need for operator downtime.

Automatically load Air Turbine Spindles® with our wrap around Toolchanger Mounting Assembly.



625 - 50,000 rpm

Superior Technology

- Unique patented direct drive with no vanes, gears or brushes to wear, burn or break.
- Cooled by turbine air for 24/7 operation. No oil or control system required. No Duty Cycle.
- Governor keeps Constant High Speed + Torque on tool path in angles and corners.

Spindle Selection

√ = Optimum

! = Dependent upon cutting conditions

∞ = Acceptable

x = Not recommended for use

		625(X)	650(X)	660(X)
Drill	Ø 0.1 - 0.3mm	√	√	√
	Ø 0.3 - 0.5mm	√	√	√
	Ø 0.5 - 1.0mm	√	√	√
	Ø 1.0 - 1.5mm	∞	√	√
	Ø 1.5 - 2.0mm	!	√	√
Endmill	Ø 0.1 - 1.0mm	√	√	√
	Ø 1.0 - 2.0mm	√	√	√
	Ø 2.0 - 3.5mm	√	√	√
	Ø 3.5 - 5.0mm	∞	√	√
	Ø 5.0 - 6.0mm	!	∞	∞
Jig Grinding		!	√	√
Specifications	625(X)	650(X)	660(X)	
Speed (rpm)	30,000 40,000 50,000 65,000	25,000 30,000 40,000	50,000	
Power (hp)	0.40 - 0.78	0.80 - 1.40	0.94 - 1.60	
T.I.R. at Nose	Less than 2µm			
Collet Range	0.5mm - 7mm			
Air Pressure	Less than 6.2 Bar (0.62 MPa)			
Air Flow	11 - 40 cfm (5.20 - 18.89 L/s) [ANR]			

