

650LCAT50 (100mm) - Spindle Series



The robust, long body **650LCAT50 (100mm)** delivers governed constant high speed and power under load - 25,000 to 40,000 rpm, < 0.88 hp (0.66 kW) with double front ceramic bearings.

The 650L (100mm) Series is ideal for heavier duty applications and milling hard materials in corners in deep pockets. The governor controlled turbine maintains rated high speed, optimizing tool performance and life. Effective in all materials, including tool steel, titanium and ceramic. Ultra low vibration and no heat in 24/7 operation.

Selectable rear or side air feed on each spindle.
Automatic Loading from the magazine on all machines.

| Dimensions | | | |
|------------|--------------|----------|----------------|
| | | | |
| A | 0.99" (25mm) | D | 5.59" (142mm) |
| B | 1.62" (41mm) | E | 9.59" (244mm) |
| C | 3.23" (82mm) | F | 13.69" (348mm) |

| 650LCAT50 (100mm) Series Spindles | | | |
|-----------------------------------|--------|------------|--------|
| ER11 - 1/4" | | ER11 - 6mm | |
| Speed RPM | Part # | Speed RPM | Part # |
| 25,000 | 64918 | 25,000 | 64919 |
| 30,000 | 64920 | 30,000 | 64921 |
| 40,000 | 64922 | 40,000 | 64923 |

| Accessories | |
|---|--------|
| Model | Part # |
| High Flow Filter / Regulator / Extractor | 30008 |
| Tube 12mm O.D. - 8mm I.D. (order by foot) | 16509 |
| Hose & Fitting - 12mm O.D. - 8mm I.D. - 12' | 30045 |

| General Specifications | 650LCAT50 (100mm) |
|--|---|
| Speed RPM | 25,000 / 30,000 / 40,000 |
| Power Rating hp (kW) | 0.80 (0.60) / 0.83 (0.62) / 0.88 (0.66) |
| Inlet Air Pressure | 90 PSI (6.2 Bar) |
| Air Consumption Idle cfm (l/s) | 13 (6.1) / 14 (6.6) / 14 (6.6) |
| Air Consumption Working Flow cfm (l/s) | 14 (6.60) - 35 (16.5) |
| Sound Level | Less Than 78 dBA |
| Max Shank Capacity | ER 11 - 1/4" (6mm) |
| Spindle Weight | 141.4 oz (4.01 kg) |

| Standard Equipment |
|---|
| Spindle, combo filter extractor (p/n #30008), collet, wrenches, hose and fittings, plug (for alternate air inlet not in use) and carrying case. ER 11 collet system (1/4" or 6mm collet standard - other sizes optional). |
| Oil free 90 psi / 6.2 bar, clean, dry air supply required. |

Tel: +1.561.994.0500 • Fax: +1.561.994.8097 • www.airturbinetools.com • info@airturbinetools.com

Do not use couplings / hoses less than 1/4" / 6mm Internal Diameter (ID). Use couplings / hoses with a minimum ID of 6.5mm for 602, 602X and 625 spindles, a minimum ID of 8mm for 625X, 650, 660 spindles and (602, 602X, 625, 625X, 650 and 660 spindles with TMA) and a minimum ID of 10mm for 650X, 660X spindles and (650X and 660X spindles with TMA). Always use a 0.3 micron filter and/or extractor where required and check specified psi or l/s air flow. Use 90 psi / 6.2 Bar clean, dry, oil-free air only. Use eye protection and follow safety instructions. Supply is subject to Air Turbine Tools Inc. terms and conditions of sale and distributor policies in effect for the time being. Subject to availability, change of specifications, price and terms without notice. All specifications approximate. Air Turbine Spindles® is the registered trade name of Air Turbine Tools, Inc. © 2017 Air Turbine Tools, Inc. All rights reserved.