

525XSV - 1/4" / 6mm Straight Hand Tool Series



Exceptionally powerful and comfortable! The **525XSV** with slide valve for quick-shut off delivers high torque at lower speeds. Double turbine power combines with lightweight, low vibration, low noise and provides greater accuracy and a finer high quality finish.

The constant high speed **525XSV** enables you to work on hard-to-reach applications for fast removal or finishing - comfortably with a light touch directing the tool. At up to 0.80 hp (0.60 kW) high speed cutting action on your work piece is assured. Patented automatic brake option stops this tool in a few seconds.

Standard Equipment: Hand Tool, 1/4" or optional 6mm collet, collet wrenches, rear exhaust, exhaust deflector, 5' air supply assembly with slide valve and 3/8" NPT air supply fitting. Oil free 90 psi / 6.2 bar, clean, dry air supply required.

Dimensions			
A	0.86" (21.84mm)	C	2.00" (50.80mm)
B	1.00" (25.40mm)	D	4.97" (126.24mm)
E	5.64" (143.26mm)	F	8.13" (206.50mm)

525XSV Series			
1/4"		6mm	
Speed RPM	Part #	Speed RPM	Part #
30,000	42530	30,000	42531
40,000	42540	40,000	42541
1/4" w/brake		6mm w/brake	
Speed RPM	Part #	Speed RPM	Part #
30,000	42534	30,000	42535
40,000	42544	40,000	42545

Accessories	
Model	Part #
High Flow Filter	30004
High Flow Filter / Regulator	30003
High Flow Filter / Regulator / Extractor	30008
5' Air Supply Assembly w/Fitting for SV Models	32207

General Specifications	525XSV
Speed RPM	30,000 / 40,000
Power Rating hp (kW)	0.80 (0.60) / 0.80 (0.60)
Inlet Air Pressure	90 PSI (6.2 Bar)
Air Consumption Idle cfm (l/s)	19 (8.97) / 20 (9.44)
Air Consumption Working Flow cfm (l/s)	22 (10.38) - 30 (14.16)
Sound Level	Less Than 67 dBA
Max Shank Capacity	1/4" (6mm)
Hand Tool Weight	15.5oz (0.44kg)

Vibration Statistics
Time to reach EAV 2.5 m/s ² A(8) 23 hours, 32 minutes
Time to reach ELV 5 m/s ² A(8) 94 hours, 6 minutes
Vibration magnitude m/s ² r.m.s 1.46

Tel: +1.561.994.0500 • Fax: +1.561.994.8097 • www.airturbine.com • info@airturbine.com

Do not use couplings/hoses less than 1/4" / 6mm Internal Diameter (ID). With 230, 525X, and 3090 units use a minimum 3/8" / 9.5mm ID coupling/hose. For 230X units use a minimum 10mm ID coupling/hose. Always use a 5 micron filter and/or extractor where required and check specified PSI or L/S air flow. Use 6.2 Bar / 90 psi clean, dry, oil-free air only. Use eye protection and follow safety instructions. Supply is subject to Air Turbine Technology Inc. (ATT) distributor policies and upon terms contained in the ATT distributor agreement. Subject to availability, change of specifications, price and terms without notice. All specifications approximate.
© 2014 Air Turbine Technology, Inc. All rights reserved.